



DIN Standard Motive Power Traction Cells

Type	Capacity		Dimensions (mm)			Cell Weight (Kgs.)		Acid Volume (Ltrs.)
	at C 5 at 30 Deg C		L	W	H	Dry	Filled	
	Ah	kWh						

XWAF RANGE

XWAF5	120	0.24	47	198	373	7.1	8.6	1.2
XWAF7	180	0.36	65	198	373	10.1	12.4	1.8
XWAF9	240	0.48	83	198	373	12.7	15.8	2.4
XWAF11	300	0.60	101	198	373	15.5	19.4	3.0
XWAF13	360	0.72	119	198	373	18.2	22.8	3.6
XWAF15	420	0.84	137	198	373	20.9	26.5	4.3
XWAF17	480	0.96	155	198	373	23.7	30.0	4.9
XWAF19	540	1.08	173	198	373	26.3	33.6	5.6
XWAF21	600	1.20	191	198	373	29.1	37.2	6.3

XWBF RANGE

XWBF5	160	0.32	47	198	428	7.7	10.1	1.8
XWBF7	240	0.48	65	198	428	11.5	14.9	2.6
XWBF9	320	0.64	83	198	428	15.0	19.4	3.4
XWBF11	400	0.80	101	198	428	18.2	23.7	4.2
XWBF13	480	0.96	119	198	428	21.7	28.2	5.0
XWBF15	560	1.12	137	198	428	25.0	32.6	5.8
XWBF17	640	1.28	155	198	428	28.5	37.1	6.6
XWBF19	720	1.44	173	198	428	31.9	41.5	7.4
XWBF21	800	1.60	191	198	428	35.2	45.9	8.2

XWCF RANGE

XWCF5	180	0.36	47	198	502	9.1	11.8	2.1
XWCF7	270	0.54	65	198	502	13.1	17.1	3.1
XWCF9	360	0.72	83	198	502	16.9	22.2	4.1
XWCF11	450	0.90	101	198	502	20.5	27.2	5.1
XWCF13	540	1.08	119	198	502	24.3	32.2	6.1
XWCF15	630	1.26	137	198	502	28.0	37.2	7.1
XWCF17	720	1.44	155	198	502	32.1	42.6	8.1
XWCF19	810	1.62	173	198	502	35.8	47.6	9.1
XWCF21	900	1.80	191	198	502	39.4	52.5	10.1

XWEF RANGE

XWEF5	220	0.44	47	198	604	11.5	14.6	2.4
XWEF7	330	0.66	65	198	604	16.3	20.9	3.6
XWEF9	440	0.88	83	198	604	20.8	26.9	4.7
XWEF11	550	1.10	101	198	604	25.2	32.8	5.9
XWEF13	660	1.32	119	198	604	29.6	38.8	7.1
XWEF15	770	1.54	137	198	604	34.3	45.1	8.3
XWEF17	880	1.76	155	198	604	38.9	51.1	9.4
XWEF19	990	1.98	173	198	604	43.2	57.0	10.6
XWEF21	1100	2.20	191	198	604	47.6	62.9	11.8

LXWEF RANGE

LXWEF5	220	0.44	47	198	575	11.5	14.4	2.4
LXWEF7	330	0.66	65	198	575	16.3	20.6	3.6
LXWEF9	440	0.88	83	198	575	20.7	26.5	4.7
LXWEF11	550	1.10	101	198	575	25.2	32.5	5.9
LXWEF13	660	1.32	119	198	575	29.5	38.4	7.1
LXWEF15	770	1.54	137	198	575	34.3	44.7	8.3
LXWEF17	880	1.76	155	198	575	37.8	49.6	9.4
LXWEF19	990	1.98	173	198	575	43.2	56.6	10.6
LXWEF21	1100	2.20	191	198	575	47.6	62.5	11.8

XWFF RANGE

XWFF5	280	0.56	47	198	755	13.2	18.1	3.8
XWFF7	420	0.84	65	198	755	19.6	26.3	5.3
XWFF9	560	1.12	83	198	755	25.4	33.9	6.8
XWFF11	700	1.40	101	198	755	31.9	41.9	8.3
XWFF13	840	1.68	119	198	755	37.2	49.4	9.8
XWFF15	980	1.96	137	198	755	42.8	57.0	11.3
XWFF17	1120	2.24	155	198	755	48.4	64.6	12.8
XWFF19	1260	2.52	173	198	755	54.1	72.1	14.3
XWFF21	1400	2.80	191	198	755	60.0	79.6	15.8

LXWFF RANGE

LXWFF5	280	0.56	47	198	725	12.8	17.7	3.8
LXWFF7	420	0.84	65	198	725	18.8	24.8	5.0
LXWFF9	560	1.12	83	198	725	24.1	31.9	6.3
LXWFF11	700	1.40	101	198	725	30.1	39.6	7.6
LXWFF13	840	1.68	119	198	725	35.3	46.6	9.0
LXWFF15	980	1.96	137	198	725	40.8	53.8	10.3
LXWFF17	1120	2.24	155	198	725	46.1	60.9	11.7
LXWFF19	1260	2.52	173	198	725	51.6	68.1	13.0
LXWFF21	1400	2.80	191	198	725	56.9	75.2	14.4